

FIG. 1




FIG. 2




FIG. 3

30

MAXIMUM NUMBER OF CUBOIDS		200,000	
DIVISION NUMBER IN X-DIRECTION	10	X-DIRECTION: TOLERANCE (mm)	0.5
DIVISION NUMBER IN Y-DIRECTION	10	Y-DIRECTION: TOLERANCE (mm)	0.5
DIVISION NUMBER IN Z-DIRECTION	10	Z-DIRECTION: TOLERANCE (mm)	0.5
BALANCED-VOLUME CONVERSION RATE	0		0.5
UNBALANCED-VOLUME CONVERSION RATE	0		0.7
REFERENCE COMPONENT		Read	Save
		Refer	PROCESS OUTLINE

FIG. 4A




FIG. 4B

MAXIMUM NUMBER OF CUBOIDS: 30




FIG. 4C

MAXIMUM NUMBER OF CUBOIDS: 150




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 12

TABLE A : OF DIMENSIONS

No.	ITEM	VALUE	ITEM	VALUE	ITEM	VALUE
1	NUMBER OF COMPONENTS	45. 0				
2-1	MAXIMUM SIZE OF COMPONENT 01:X	15. 0	MAXIMUM SIZE OF COMPONENT 01:Y	23. 0	MAXIMUM SIZE OF COMPONENT 01:Z	50. 0
2-2	MAXIMUM SIZE OF COMPONENT 02:X	21. 0	MAXIMUM SIZE OF COMPONENT 02:Y	10. 0	MAXIMUM SIZE OF COMPONENT 02:Z	78. 0
...						
2-n	MAXIMUM SIZE OF COMPONENT 0n:X	10. 0	MAXIMUM SIZE OF COMPONENT 0n:Y	23. 0	MAXIMUM SIZE OF COMPONENT 0n:Z	36. 0
...						
2-45	MAXIMUM SIZE OF COMPONENT 45:X	80. 0	MAXIMUM SIZE OF COMPONENT 45:Y	55. 0	MAXIMUM SIZE OF COMPONENT 45:Z	86. 0
3	SIZE OF DEVICE:X	260. 0	SIZE OF DEVICE:Y	450. 0	SIZE OF DEVICE:Z	350. 0

FIG. 13

TABLE B : VALUES OF PHYSICAL PROPERTIES

No.	ITEM	NAME	MATERIAL	VALUE OF PHYSICAL PROPERTY 1	VALUE OF PHYSICAL PROPERTY 2	VALUE OF PHYSICAL PROPERTY 3
4-1	COMPONENT:01	PCB	EPOXY RESIN	0. 3	1. 4	1190
4-2	COMPONENT:02	PCB	EPOXY RESIN	0. 3	1. 4	1190
...						
4-n	COMPONE:0n	COVER	STEEL	43. 0	0. 5	7850
...						
4-45	COMPONE:45	DEVICE	CERAMIC	36. 0	0. 8	3890

FIG. 14




FIG. 15A




FIG. 15B




FIG. 16

O SCALE OF DEVICE			
<input type="checkbox"/>	LARGE-SIZED SERVER		
<input checked="" type="checkbox"/>	SMALL/MEDIUM-SIZED DEVICE		
<input type="checkbox"/>	PERSONAL COMPUTER		
<input type="checkbox"/>	MAGNETIC DISK		
<input type="checkbox"/>	MOBILE TELEPHONE		
O IMPLEMENTATION FORM			
<input checked="" type="checkbox"/>	HIGH DENSITY		
<input type="checkbox"/>	MEDIUM DENSITY		
<input type="checkbox"/>	LOW DENSITY		
O CONDUCTIVITY			
<input checked="" type="checkbox"/>	HIGH CONDUCTIVITY		
<input type="checkbox"/>	MEDIUM CONDUCTIVITY		
<input type="checkbox"/>	LOW CONDUCTIVITY		
<input type="checkbox"/>	NONCONDUCTIVITY		
<table border="1"><tr><td>EDIT</td><td>SELECT</td></tr></table>		EDIT	SELECT
EDIT	SELECT		

FIG. 17

PARAMETER KIT SELECTION TABLE

	KIT 1	KIT 2	KIT 3	KIT 4
OSCALE OF DEVICE				
<input type="checkbox"/> LARGE-SIZED SERVER	○			
<input checked="" type="checkbox"/> SMALL/MEDIUM-SIZED DEVICE		○		
...				○
<input type="checkbox"/> MOBILE TELEPHONE			○	
OIMPLEMENTATION FORM				
<input checked="" type="checkbox"/> HIGH DENSITY		○	○	
...				○
<input type="checkbox"/> LOW DENSITY	○			
OCONDUCTIVITY				
<input checked="" type="checkbox"/> HIGH CONDUCTIVITY	○	○		
...			○	
<input type="checkbox"/> NONCONDUCTIVITY				○

FIG. 18A




FIG. 18B




FIG. 18C

MAXIMUM X-VALUE	5.0
MAXIMUM Y-VALUE	3.5
MAXIMUM Z-VALUE	3.5

FIG. 19

MAXIMUM NUMBER OF CUBOIDS: xxxx	
DIVISION NUMBER IN X-DIRECTION: XX	CONVERSION TIME: _____ MINUTES
DIVISION NUMBER IN Y-DIRECTION: YY	
DIVISION NUMBER IN Z-DIRECTION: ZZ	
TOTAL NUMBER OF DIVISIONS: SSSS	<div>Close</div>

FIG. 20





FIG. 21

TABLE C : OF PARAMETERS

No.	ITEM	VALUE	ITEM	VALUE	ITEM	VALUE
1	MAXIMUM NUMBER OF CUBOIDS	200				
2	NUMBER OF MESH-DIVISION : X	20	NUMBER OF MESH-DIVISION : Y	40	NUMBER OF MESH-DIVISION Z	20
3	TOLERANCE: X	0. 5	TOLERANCE: Y	0. 5	TOLERANCE: Z	0. 5
4	BALANCED-VOLUME CONVERSION RATE	0. 4				
5	UNBALANCED- VOLUME CONVERSION RATE	0. 7				
6	SIZE OF REFERENCE COMPONENT: X	65. 0	SIZE OF REFERENCE COMPONENT: Y	32. 0	SIZE OF REFERENCE COMPONENT: Z	50. 0

FIG. 22



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.